



Corrigendum to ‘Removal of iodide from water using halloysite/Ag₂O composites as efficient adsorbent’ [Applied Clay Science 213 (2021) 106241]



Wenbin Yu ^{a,b}, Quan Wan ^{a,b,c,*}, Daoyong Tan ^d, Shuguang Yang ^{a,b}, Zonghua Qin ^{a,b}, Xin Nie ^{a,b}

^a State Key Laboratory of Ore Deposit Geochemistry, Institute of Geochemistry, Chinese Academy of Sciences, Guiyang, Guizhou 550081, China

^b University of Chinese Academy of Sciences, Beijing 100049, China

^c CAS Center for Excellence in Comparative Planetology, Hefei 230026, China

^d Key Laboratory of Solid Waste Treatment and Resource Recycle, Ministry of Education, Southwest University of Science and Technology, Sichuan, Mianyang 621010, China

The authors regret that due to the misuse of the molar mass of Ag₂O, there is an error in the above article: in 3.1, the equation used to estimate the Ag₂O contents of the composites, $W_s = (V_{\text{total-Hal}} \div 1000 \times C_{\text{silver nitrate}} \times 127) / (V_{\text{total-Hal}} \div 1000 \times C_{\text{silver nitrate}} \times 127 + 1)$ should be $W_s = (V_{\text{total-Hal}} \div 1000 \times C_{\text{silver nitrate}} \times 115.9) / (V_{\text{total-Hal}} \div 1000 \times C_{\text{silver nitrate}} \times 115.9 + 1)$, where, 115.9 is half of the molar mass of Ag₂O.

Accordingly, the W_s values of Hal-Ag₂O-1 and Hal-Ag₂O-2 (0.98 and 2.42% in the article) should be 0.90 and 2.21%, respectively. The Q_{m-s} values of Hal-Ag₂O-1 and Hal-Ag₂O-2 (1369.50 and 1642.36 mg/g in the article) should be 1499.82 and 1796.38 mg/g, respectively.

The authors would like to apologise for any inconvenience caused.

DOI of original article: <https://doi.org/10.1016/j.clay.2021.106241>.

* Corresponding author.

E-mail address: wanquan@vip.gyig.ac.cn (Q. Wan).